

# RANGER XP 1000 Premium Super Graphite with Lifted Lime Accents



## Key Specifications

**82**  
HP

**62.5"**  
WIDTH

**13"**  
GROUND CLEARANCE

## ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	82 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

## DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,000 lb (454 kg)
Dry Weight	1,625 lb (737 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	13 in (33 cm)
GVW	3,600 lb (1,632.9 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 77 in (305 x 158 x 196 cm)
Payload Capacity	1,500 lbs (680.4 kg)
Person Capacity	3

<b>Wheelbase</b>	81 in (206 cm)
------------------	----------------

## BRAKES

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
<b>Parking Brake</b>	Park In-Transmission

## ADDITIONAL SPECIFICATIONS

<b>Adjustable Driver Seat</b>	Standard
<b>Cargo System</b>	Lock & Ride®
<b>Color / Graphics</b>	Super Graphite with Lifted Lime Accents
<b>Electronic Power Steering</b>	Standard
<b>Instrumentation</b>	Dual-sweep Analog Dials w/ 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, 1 DC Outlet, 1 USB Charge Port
<b>Lighting</b>	Dual LED Headlamps, 1250 lm Low Beam, 2300 lm High Beam, Dual LED Taillamps
<b>Other Standard Features</b>	Premium Cut & Sew Seats with Contoured Seatbacks and Embroidered Polaris Branding, Premium Steering Wheel and Interior Accents, Polaris Pulse Electrical System (6 position), Standard In-Dash SAE Charge Port, NFC Front Badge
<b>RIDE COMMAND+</b>	Available
<b>Tilt Steering</b>	Standard

## TIRES / WHEELS

<b>Front Tires</b>	27 x 9-14; Pro Armor X-Terrain
<b>Rear Tires</b>	27 x 11-14; Pro Armor X-Terrain
<b>Tire Ply Rating</b>	8 Ply Rated
<b>Wheels</b>	14" Aluminum

## SUSPENSION

<b>Front Suspension</b>	Dual A-Arm 11 in (27.9 cm) Travel
<b>Rear Suspension</b>	Dual A-Arm, IRS 11 in (27.9 cm) Travel
<b>Turning Radius</b>	13.3 ft (406.4 cm)